

FinishLine II™

GRAVITY FEED SPRAY GUNS



- **Economically-priced**
- **Available in HVLP or conventional models**
- **Durable, high quality construction**
High grade aluminum gun body
NEW! Aluminum retaining ring and adjusting knobs
NEW! Replaceable threaded baffle for economical servicing
Alloyed resin handle keeps gun weight to a minimum
Gun washer safe
- **Precision engineered to produce well-atomized, uniform spray patterns**
- **Accurate, repeatable settings**
Pointers on fluid and fan controls
- **Stainless steel fluid needle and alloy resin fluid tip**
- **Less time spent on refills**
NEW! 32 oz. aluminum cup with disposable, push-on lid
- **Quick clean-up and upside-down spraying with no cup leaks** with E-Z Liner™ disposable cup liners
- **Includes:**
32 oz. aluminum cup (120175/GFC-502)
(4) E-Z Liner™ disposable cup liners (190966/OMX-70-K48)
1.4 mm fluid tip (conventional gun)
1.4 mm and 1.6 mm fluid tips (HVLP gun)
Air adjusting valve with gauge (180006/HAV-501) (HVLP gun)
Gun hook, spray lube, fluid filter

Specifications

HVLP Model

23 psi inlet pressure delivers
10 psi air cap pressure
at 11.4 cfm air volume

Note: Gun trigger must be pulled when adjusting air inlet pressure.

519210 (FLG-463) Air Cap Test Kit

Conventional Model

9.9 cfm at 40 psi inlet pressure

FinishLine Gravity Feed Spray Guns

Order No. Model No.	Type	Fluid Tip (mm)	Air Cap	Applications
611103 FLG-635-316	HVLP	1.6/1.4*	#3	General purpose, light to heavy viscosity materials
611101 FLG-615-114	Conventional	1.4	#1	General purpose, light to heavy viscosity materials

*HVLP models come standard with two sizes of fluid tips.